

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 May 2004 (21.05.2004)


PCT

(10) International Publication Number
WO 2004/042987 A1

- (51) International Patent Classification⁷: H04L 1/00, 29/08, H04B 7/00, H04Q 7/22
- (21) International Application Number: PCT/EP2002/012426
- (22) International Filing Date: 7 November 2002 (07.11.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): PEDERSEN, Kent [DK/DK]; Borups Alle 109 3.th, DK-2000 Frederiksberg (DK). SEBIRE, Benoist [FR/FI]; Sateentie 4, FIN-02100 Espoo (FI).
- (74) Agents: DERRY, Paul et al.; Venner, Shipley & Co., 20 Little Britain, London EC1A 7DH (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TRANSPORT FORMAT DATA TRANSMISSION



(57) Abstract: In a flexible layer one (403) of a GERAN transmitter device, a TFCI, which indicates a particular combination of cyclic redundancy check, channel coding and rate matching, is generated by a TFCI generating process (412) using information from the medium access control layer. The TFCI is coded by a coding process (413), and inserted into the data stream by a TFCI insertion process (414). Each code has more bits than the corresponding TFCI, and identifies uniquely the TFCI. The coded TFCI is spread across the pre-interleaved block with portions placed in fixed positions in each burst. Interleaving is then performed by an interleaver (411). The coded TFCI used with a half-rate channel is the central segment of the coded TFCI used in the corresponding full-rate channel. The additional loss is so small as to be insignificant, but the FER performance is significantly improved, compared to using the full-rate codes, as a result of the increased payload of the content data bits. In half-rate mode, the amount of coded TFCI data gives rise to a ratio of the performance of the coding of the transport format combination data to the performance of the coded content data which is at a similar level to the ratio in the full-rate mode.